Packaging Requirements Sheet
(Special Packaging Instructions) DS6411

PRON: S61ZA711SBM1 DATE: 8 MAR 2001

NSN: 5340-01-432-7686

MILSTRIP: SUE LERCH/28202

A. Military preservation, packing, and marking for the item identified above shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 DEC 99, and the Special Packaging Instruction contained in the TDP.

PRESERVATION: MILITARY
LEVEL OF PACKING: B
QUANTITY PER UNIT PACKAGE: 001
SPI NUMBER P31-15-4708, DATED 21 APR 95

B. Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.

C. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129 Revision N, Date 15 May 97, including bar coding iaw ANSI/AIM-BC1, Uniform Symbology Specification Code 39.

D. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in Paragraph E below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.

E. SUPPLEMENTAL INSTRUCTIONS: THE GROSS WEIGHT AND TOTAL QUANTITY PER PALLET SHALL BE PLACED ON A MARKING BOARD/PANEL AND SECURELY ATTACHED ON TWO ADJACENT SIDES.

Packaging Requirements Sheet
(Special Packaging Instructions) DS6411

PRON: S61ZA712SBM1 DATE: 8 MAR 2001

NSN: 5340-01-422-7630

MILSTRIP: SUE LERCH/28202

A. Military preservation, packing, and marking for the item identified above shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 DEC 99, and the Special Packaging Instruction contained in the TDP.

PRESERVATION: MILITARY
LEVEL OF PACKING: B
QUANTITY PER UNIT PACKAGE: 001
SPI NUMBER P31-15-4707, DATED 21 APR 95

B. Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.

C. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129 Revision N, Date 15 May 97, including bar coding iaw ANSI/AIM-BC1, Uniform Symbology Specification Code 39.

D. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in Paragraph E below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.

E. SUPPLEMENTAL INSTRUCTIONS: THE GROSS WEIGHT AND TOTAL QUANTITY PER PALLET SHALL BE PLACED ON A MARKING BOARD/PANEL AND SECURELY ATTACHED ON TWO ADJACENT SIDES.