

Battery, Primary, Cylindrical -- Lithium Thionyl Chloride  
International Size Reference: C, Standard Termination

Technical Requirements:

1. Nominal Capacity @ 3 mA to 2 V: Minimum of 7 Ah
2. Rated Voltage (nominal): 3.6 V
3. Dimensions:
  - A. Battery Overall Height: 48.5 mm (minimum), 50 (maximum)
  - B. Battery Diameter: 24.9 mm (minimum), 26.2 mm (maximum)
4. Operating Temperature Range: - 40° C to + 65° C
5. Storage Temperature Range: - 50° C to + 70° C
6. Battery Shall Be Recognized By Underwriters Laboratories, Inc. Under UL Standard 1642 As "User-Replaceable."
7. Battery Shall Be Non-Restricted or Shall Meet: (a) the Exemptions of Title 49, Part 173, Section 173.185, Lithium Batteries and Cells and (b) the International Air Transport Association (IATA) Regulations.

SUGGESTED SOURCES OF SUPPLY		
CAGE CODE	Part Number	Name And Address
0BYG1	TL-2200	Tadrian Electronic Industries 2 Seaview Blvd. Ste 102 Port Washington, NY 11050-4634
0BYG1	TL-5920	Tadrian Electronic Industries, Inc. 2 Seaview Blvd. Ste 102 Port Washington, NY 11050-4634

**BRAND NAME OR EQUAL**