

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, Va 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503. Please do not return your form to either of these addresses.

1. PART OR DRAWING NO. NOMENCLATURE 9398994 BLADDER		2. CODE INDENT 19200		3. SPI NO. (AM) P9398994	
4. NATIONAL STOCK NO. 2590-01-416-6248		5. DATE OF DRAWING/SPI (YYMMDD)		6. REVISION / ERR NO. A /	
7. QUP / UNIT OF ISSUE 1/EA	8. ICQ	9. UNIT PACK WT. (LB) (0.0) 2.5	10. UNIT PACK CU (CU. FT.) (0.000) 0.519	11. UNIT PACK SIZE (INCHES) (00.0) 14.0 x 8.0 x 8.0	
		18. STEPS	19. REQD	20. DESCRIPTION	
12. MILITARY PRESERVATION MIL-STD-2073-1, METHOD 41		1		SEE NOTE A	
13. CLEANING *		2	1	COLLAR, SEE NOTE B	
		3	1	BAG, SEE NOTE C	
		4	AR	CUSHIONING, ASTM D59135, DOUBLE WRAP BAG	
14. DRYING *		5	1	CONTAINER, ASTM D5118, STYLE RSC, TYPE COR, GRADE V3C, CLASS WR, SEE NOTE D	
15. PACKING		6		CLOSURE, ASTM D 1974,, SEALING METHOD B	
a. LEVEL A MIL-STD-2073-1C					
b. LEVEL B MIL-STD-2073-1C					
16. MARKING MIL-STD-129					

17. NOTES/DRAWING
* UNLESS OTHERWISE SPECIFIED, CLEANING AND DRYING SHALL BE IN ACCORDANCE WITH PARAGRAPH 5.2.1 OF MIL-STD-2073-1. WEIGHTS AND SIZES ARE ESTIMATED AND MAY VARY SLIGHTLY. INTERMEDIATE PACKAGING AND PACKING WILL BE IN ACCORDANCE WITH SPECIFICATION MIL-STD-2073-1 OR AS OTHERWISE SPECIFIED HEREIN.

- A) PURGE BLADDER WITH NITROGEN AND FILL BLADDER WITH NITROGEN TO ONE(1) POUND PER SQUARE INCH PRESSURE.
- B) PLACE A SNUG FITTING SOLID FIBERBOARD COLLAR OVER THE GAS VALVE ASSEMBLY. THE COLLAR SHALL EXTEND BEYOND THE LENGTH OF THE GAS VALVE ASSEMBLY.
- C) THE BAG SHALL BE WATERVAPORPROOF HEAT-SEALABLE BLACK PLASTIC, A MINIMUM OF 5 MILS THICK. PLACE THE BLADDER INTO THE BAG, EVACUATE EXCESS AIR FROM THE BAG, PURGE THE BAG WITH NITROGEN, AND HEAT SEAL CLOSE.
- D) ADD SPECIAL MARKING: DO NOT STORE ABOVE 70 DEGREES FAHRENHEIT.

WSC: KF ITEM SIZE: 13.82 x 7.76 x 7.76 ITEM WEIGHT: 2.00 APPROVED:

STATEMENT A, UNLIMITED