



3.4.47 SOCKET WRENCH, 1/4 INCH SQ DR, (.343). 11/32 IN WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.48 SOCKET WRENCH, 1/4 INCH SQ DR, (.375). 3/8 IN WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.49 SOCKET WRENCH, 1/4 INCH SQ DR, (.437). 7/16 IN WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.50 SOCKET WRENCH, 1/4 INCH SQ DR, (.500). 1/2 IN WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.51 SOCKET WRENCH, 1/4 INCH SQ DR, (.562). 9/16 IN WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.52 SOCKET WRENCH, 1/4 INCH SQ DR, (10). 10 MM WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.53 SOCKET WRENCH, 1/4 INCH SQ DR, (13). 13 MM WRENCH SIZE, STANDARD LENGTH, 12 PT, CHROME OR SATIN



3.4.54 SOCKET WRENCH, 3/8 INCH SQ DR, (.437). 7/16 INCH WRENCH SIZE, 12 PT, STD LENGTH, Chrome Or Satin



3.4.55 SOCKET WRENCH, 3/8 INCH SQ DR, (.437), DEEP REACH. 3/8 INCH SQ DR, 7/16 INCH WRENCH SIZE, 12 PT, DEEP REACH, CHROME OR SATIN



3.4.56 SOCKET, 3/8 IN SQ DR (0.500): 1/2 INCH WRENCH SIZE, 12 PT, STD LENGTH, CHROME OR SATIN



3.4.57 SOCKET, 3/8 IN SQ DR (0.562): 9/16 INCH WRENCH SIZE, 12 PT, STD LENGTH, CHROME OR SATIN



3.4.58 SOCKET WRENCH, 3/8 INCH SQ DR (.562), DEEP REACH. 9/16 INCH WRENCH SIZE, 12 PT, DEEP REACH, CHROME OR SATIN



3.4.59 SOCKET, SOCKET WRENCH, 3/8 IN SQ DR (.626). 5/8 IN WRENCHING SIZE, STEEL, 12 PT, CHROME OR SATIN FINISH, STANDARD LENGTH



3.4.60 SOCKET, SOCKET WRENCH, 3/8 IN SQ DR (.688). 11/16 IN WRENCHING SIZE, STEEL, 12 PT, CHROME OR SATIN FINISH, STANDARD LENGTH



3.4.61 SOCKET, SOCKET WRENCH, 3/8 IN SQ DR (.750). 3/4 IN WRENCHING SIZE, STEEL, 12 PT, CHROME OR SATIN FINISH, STANDARD LENGTH



3.4.62 SOCKET, SOCKET WRENCH, 3/8 IN SQ DR (.813). 13/16 IN WRENCHING SIZE, STEEL, 12 PT, CHROME OR SATIN FINISH, STANDARD LENGTH



3.4.63 SOCKET, SOCKET WRENCH, 3/8 IN SQ DR (.875). 7/8 IN WRENCHING SIZE, STEEL, 12 PT, CHROME OR SATIN FINISH, STANDARD LENGTH



3.4.64 SOCKET, SOCKET WRENCH, 3/8 IN SQ DR (.938). 15/16 IN WRENCHING SIZE, STEEL, 12 PT, CHROME OR SATIN FINISH, STANDARD LENGTH



3.4.65 HOLDER, BIT SCREWDRIVER. 1/4 IN SQ DRIVE TO 1/4 IN HEX DRIVE



3.4.66 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.094). 3/32 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" IN OVERALL LENGTH



3.4.67 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.109). 7/64 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.68 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.125). 1/8 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.69 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.141). 9/64 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.70 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.156). 5/32 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.71 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.187). 3/16 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.72 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (0.219). 7/32 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL



3.4.73 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (2.5). 2.5 MM WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH.



3.4.74 SOCKET, MALE HEX KEY, 1/4 IN SQ DR (3). 3 MM WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.75 SOCKET, MALE HEX KEY, 3/8 IN SQ DR (0.375). 3/8 IN WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.76 SOCKET, MALE HEX KEY, 3/8 IN SQ DR (4). 4 MM WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.77 SOCKET, MALE HEX KEY, 3/8 IN SQ DR (5). 5 MM WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.78 SOCKET, MALE HEX KEY, 3/8 IN SQ DR (6). 6 MM WRENCHING SIZE, BIT EXPOSURE 1", MINIMUM, 2"  $\pm$  .125" OVERALL LENGTH



3.4.79 SOCKET, CROWSFOOT ATTACHMENT (.375). 1/4 IN SQ DR, 3/8 IN WRENCHING SIZE



3.4.80 SOCKET, CROWSFOOT ATTACHMENT (.500). 1/4 IN SQ DR, 1/2 IN WRENCHING SIZE



3.4.81 SOCKET, CROWSFOOT ATTACHMENT (14). 3/8 IN SQ DR, 14 MM WRENCHING SIZE



3.4.82 SCREWDRIVER ATTACHMENT, HI-TORQUE, SOCKET WRENCH, FLAT TIP. 1/4 IN SQ DR, TIP SIZE #3 (.058" N TIP THICKNESS X .372 IN WIDE), TORQUE CAPACITY 100 IN LBS



3.4.83 SOCKET, SOCKET WRENCH, UNIVERSAL JOINT, 1/4 IN SQ DR, CHROME OR SATIN.



3.4.84 SOCKET, SOCKET WRENCH, UNIVERSAL JOINT, 3/8 in SQ DR. CHROME OR SATIN



3.4.85 ADAPTER, SOCKET WRENCH, 1/4" MALE TO 3/8" FEMALE. 3/8 IN DRIVE SOCKET WRENCH ADAPTER TO 1/4" DRIVE SOCKET, CHROME OR SATIN



3.4.86 ADAPTER, SOCKET WRENCH, 3/8" MALE TO 1/4" FEMALE. 3/8 IN DRIVE SOCKET WRENCH ADAPTER TO 3/8" DRIVE SOCKET, CHROME OR SATIN



3.4.87 ADAPTER, SOCKET WRENCH, 1/2" MALE TO 3/8" FEMALE. 1/2 IN DRIVE SOCKET WRENCH ADAPTER TO 3/8" DRIVE SOCKET, CHROME OR SATIN



3.4.88 WRENCH BOX (.219). 7/32 WRENCHING SIZE ONE END, 15/64 IN WRENCHING SIZE ON OPPOSITE END, CHROME OR SATIN FINISH



3.4.89 WRENCH BOX/OPEN (.187). 3/16 IN WRENCHING SIZE, 6 OR 12 PT, OFFSET, CHROME OR SATIN FINISH



3.4.90 WRENCH BOX/OPEN (.219). 7/32 IN WRENCHING SIZE, 6 OR 12 PT OFFSET, CHROME OR SATIN FINISH



3.4.91 WRENCH BOX/OPEN (.250). 1/4 IN WRENCHING SIZE, 12 PT OFFSET, CHROME OR SATIN FINISH



3.4.92 WRENCH BOX/OPEN (.281). 9/32 IN WRENCHING SIZE, 6 OR 12 PT OFFSET, CHROME

OR SATIN FINISH



- 3.4.93 WRENCH BOX/OPEN (.312). 5/16 IN WRENCHING SIZE, 12 PT OFFSET, CHROME OR SATIN, 3.25 - 5.5" LONG



- 3.4.94 WRENCH BOX/OPEN (.344). 11/32 IN WRENCHING SIZE, 12 PT OFFSET, CHROME OR SATIN, 3.25 - 5.75" LONG



- 3.4.95 WRENCH BOX/OPEN (.375). 3/8 IN WRENCHING SIZE, 12 PT OFFSET, CHROME OR SATIN, 4.188 - 6.0" LONG



- 3.4.96 WRENCH BOX/OPEN (.437). 7/16 IN WRENCHING SIZE, 12 PT OFFSET, CHROME OR SATIN, 4.969 - 7.0" LONG



- 3.4.97 WRENCH BOX/OPEN (.500). 1/2 IN WRENCHING SIZE, 12 PT OFFSET, CHROME OR SATIN, 5.250 - 8.0" LONG