

SPECIAL PACKAGING INSTRUCTION (AMCCOM Suppl 1 to AR 700-15) **NATIONAL STOCK NUMBER** 4240-01-331-0170

NOMENCLATURE
LINER, NBC, ROOM PACKAGE **UI** **CLEANING/DRYING** **SPI NUMBER (PN)**
 EA C1/ANY P5-19-11334

LEVEL A UNIT PACK REQUIREMENTS (MIL-P-116 METHOD III)	STEPS	DRAWING OR SPECIFICATION	STYLE	TYPE	GRADE	CLASS	SIZE AND REMARKS (INCHES)
Liner (bag)	(A) 1	PPP-B-26	1	II			36 x 50
Container (box)	(C) 2	PPP-B-636	RSC		V3c	WR	41 x 26 x 10
Dunnage	(B) 3	PPP-C-850		I	R	*	As Required
Closure (step 2)	4	PPP-B-636					Appendix (closure method V and reienforced IAW reinforcing requirements)
							* optional

LEVEL B (METHOD) NOT APPLICABLE SEE NOTE IAW MIL-STD-2073-1
 LEVEL C (METHOD) NOT APPLICABLE SEE NOTE IAW MIL-STD-2073-1
 COMMERCIAL PACKAGING NOT APPLICABLE SEE NOTE IAW ASTM D3951

UNIT PACK LOGISTICS DATA (Weights and Sizes Approximate)

LEVEL	UNIT PACK QUANTITY	UNIT PACK WEIGHT	UNIT PACK CUBE	UNIT PACK SIZE (EXTERIOR) FEET
A	1	46.70	6.755 cu. ft.	3.45 x 2.20 x .89

Intermediate packaging and packing will be in accordance with specification MIL-STD-2073-1 or as otherwise specified hereon. (C)
 Marking will be in accordance with MIL-STD-129.

Specifications, standards, and drawings listed hereon of the issue in effect on date of invitation for bid form a part of this data sheet. The applicable general and referenced requirements of specification MIL-STD-2073-1 form part of this data sheet. Unless otherwise specified, materials will be minimum size IAW MIL-STD-2073-1.

Tolerances shall be in accordance with material specifications. Quality performance and testing requirements shall be in conformance with MIL-STD-2073-1 or as specified hereon. (D)

REMARKS/ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.

- (A) - Insert liner package, in the configuration shown on Dwg. 5-19-11334, into specified bag (step 1) and close bag by folding the opening over onto the body of the liner package. Secure with PPP-T-60 tape (2 WD), as required. As an alternate to the bag liner, a wrap conforming to L-P-378 (.006 thick) may be used and shall cover the item with one complete wrap of material with a minimum overlap of four inches. The seams, which are formed by overlapped material, shall be completely sealed with tape specified above. Insert the bagged/wrapped liner package into box (step 2) and close (step 3). Note: tearing of liner bag/wrap during the packaging operation is permitted.
- (B) - Prior to final closure of box (item 2), add specified dunnage as necessary to fill voids in box.
- (C) - The unit pack box may serve as the Level B shipping container.

Original Preparer: JL McNerney 30 Jun 92		Revised by: John L. McNerney / 2 Jan 02				
ITEM DATA (APPROX) ITEM CODE - Z24	AMCCOM 81361		JLM	Z24-0418-001	Z24-174 A	2 Jan 02
	SCBRD-ENE		lnh	S2L0716-01	Z24-075	12 Oct 94
ITEM SIZE - 39 x 24 x 8 (folded and assembled in carrier bag)	PAGE NUMBER	NUMBER OF PAGES		S3K1510-002		
ITEM WEIGHT - 37.00 lbs	1	2	S3L1562-002	APPROVAL		REVISION
			S3L1591-001			DATE

Attachment 009 X

SPECIAL PACKAGING INSTRUCTION(Continued)

NATIONAL STOCK NUMBER
4240-01-331-0170

SPI NUMBER (PN)
P5-19-11334

- (D) - The preproduction (first article) and quality conformance inspection and testing requirements for level A unit packing shall be in accordance with EA-L-1595; packing inspection shall be in accordance with the quality conformance inspection requirements of MIL-STD-2073-1.
- (E) - **Interplant shipment.** Packaging and marking for interplant shipment (commercial) shall only be used as indicated in EA-L-1595.

- (F) - **SHELF LIFE.** Shelf life markings shall be applied.

NOMENCLATURE
LINER, NBC, ROOM PACKAGE

PAGE NUMBER
2

NUMBER OF PAGES
2