99-R-0197

NOTICE OF REVISION (NOR)

THIS REVISION DESCRIBED BELOW HAS BEEN AUTHORIZED FOR THE DOCUMENT LISTED.

1. DATE (YYMMDD): 990527

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

PLEASE DO NOT RETURN YOUR COMPLETED FORM TO EITHER OF THESE ADDRESSES. RETURN COMPLETED FORM TO THE GOVERNMENT ISSUING CONTRACTING OFFICER FOR THE CONTRACT/ PROCURING ACTIVITY NUMBER LISTED IN ITEM 2 OF THIS FORM.

2. PROCURING ACTIVITY NO.: 123-0065

3. DODAAC:

4. ORIGINATOR

a. TYPED NAME (First, Middle Initial, Last): Nancy Waltman

b. ADDRESS (Street, City, State, Zip Code): Cdr, CBCCOM, ATTN: AMSSB-REN-SS, APG-EA, MD 21010-5424

5. CAGE CODE: 81361

6. NOR NO.: 001

7. CAGE CODE: 81361

8. DOCUMENT NO.: P5-1-2802

9. TITLE OF DOCUMENT: HOOD ASSEMBLY

10. REVISION LETTER: a. CURRENT: b. NEW: A

11. ECP NO.: 123-0065

12. CONFIGURATION ITEM (OR SYSTEM) TO WHICH ECP APPLIES: MASK, M45

Sht 1 of 3

13. DESCRIPTION OF REVISION

THIS CHANGE IS AGAINST THE ORIGINAL DOCUMENT

REVISE SPI AS SHOWN ON THE ATTACHED COPY

14. THIS SECTION FOR GOVERNMENT USE ONLY

a. (X one)

- [X] (1) Existing document supplemented by this NOR may be used in manufacture.
- [ ] (2) Revised document must be received before manufacturer may incorporate this change.
- [ ] (3) Custodian of master document shall make above revison and furnish revised document.

b. ACTIVITY AUTHORIZED TO APPROVE CHANGE FOR GOVERNMENT: AMSSB-PM-RNN-C

c. TYPED NAME (First, Middle Initial, Last): DON KILDUFF

d. TITLE: M45 SYSTEM MANGER

e. SIGNATURE: [signature]

f. DATE SIGNED (YYMMDD): 990611

15. a. ACTIVITY ACCOMPLISHING REVISION

b. REVISON COMPLETED (Signature)

c. DATE SIGNED (YYMMDD)

DD Form 1695, APR 92 — Previous editions are obsolete.

DISTRIBUTION STATEMENT A. Approved for Public Release. Distribution is unlimited.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

SPECIAL PACKAGING INSTRUCTION (SPI) *(A)*

NATIONAL STOCK NUMBER 4240-01-441-0553

NOMENCLATURE **HOOD ASSEMBLY**	UI	QUP	SPI NUMBER (PN)
	EA	1	P5-1-2802

Cleaning & Drying shall be in accordance with Para 5.2.1 of MIL-STD-2073-1C

UNIT PACK LEVEL A REQUIREMENTS (MIL STD 2073-1 Method)	STEPS	DRAWING OR SPECIFICATION	STYLE	TYPE	GRADE	CLASS	SIZE AND REMARKS (INCHES)
TALCUM	(B) 1	U-T-30					As required
BAG, LINER	(B) 2	PPP-B-26					2 1/2 x 3 x .003 thk-2 required
RUBBER BAND	(B) 3	A-A-131					2 reqd (see note for option)
BAG (B	(C) 4	MIL-B-117					11 x 7 x .004 thk
CLOSURE	(C) 5						Heat Seal

☒ Level B (Method) ☐ See Note ☒ In accordance with MIL-STD-2073-1

INTERMEDIATE PACKAGING AND PACKING
☒ In accordance with MIL-STD-2073-1
☐ As specified hereon.

MARKING
☒ In accordance with MIL-STD-2073-1 (D)
☐ As specified hereon.

QUALITY PERFORMANCE and TESTING REQUIREMENTS
☒ In accordance with MIL-STD-2073-1, Appendices F & G
☐ As specified hereon.

Unless otherwise specified, materials shall be minimum size in accordance with MIL-STD-2073-1. Tolerances shall be in accordance with material specifications.

UNIT PACK LOGISTICS DATA (Weights and Sizes Approximate)

LEVEL	UNIT PACK QUANTITY	UNIT PACK WEIGHT	UNIT PACK CUBE	UNIT PACK SIZE (EXTERIOR) FEET
A	1	.70 lbs	.167 cu.ft.	.95 x .65 x .27
B	1			

REMARKS/ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
++

(A) – ***THIS SPI IS NOT APPLICABLE FOR INTERPLANT SHIPMENTS.*** Packaging and marking for interplant shipment is for supplies and materials that do not directly enter the military supply system. Typical interplant shipments are shipments from a vendor to a subcontractor or a prime contractor, or between contractors and subcontractors, or from a vendor or contractor to a military arsenal, plant, or other activity for evaluation, immediate use, or further processing as specified in the applicable contract.

(B) – Prior to unit packing, prepare each hood assembly as follows:

- Lightly dust the interior and exterior of hood with specified talc (step 1).
- Lay the hood out flat facing upward and with the strap assemblies extended away from the hood body. Fold hood in half with the strap and buckle assemblies extending below the folded assembly. Remove as many wrinkles from the assembly as practicable.
- Insert the extended strap and buckle assemblies into bag (step 2) and secure each bag opening around the strap above buckle with a rubber band conforming to A-A-131, Size No. 18 (step 3). As an option, each bag may be secured with tape conforming to ASTM D5486.

ITEM DATA (APPROX)	*Original Preparer:* stallings/williamson		*Revised by: nj waltman/May 1999*		
ITEM CODE 123	SBCCOM 81361 AMSSB-REN-SS				
ITEM SIZE – 5 1/2 x 4 1/2 x 3 (approx folded dim)					
ITEM WEIGHT – .57 LBS	PAGE NUMBER 1	NUMBER OF PAGES 2	APPROVAL	REVISION	DATE

DISTRIBUTION STATEMENT A: Approved for public release, distribution unlimited.

SPECIAL PACKAGING INSTRUCTION		NATIONAL STOCK NUMBER 4240-01-441-0553
NOMENCLATURE **HOOD ASSEMBLY**	PAGE NUMBER 2 of 2	SPI NUMBER (PN) P5-1-2802

- With the hood laid out flat as as described above, fold hood assembly in fourths, inserting the extended straps (wrapped) within the folds. Next, roll the folded assembly tightly to produce a rolled configuration with an approximate dimension of 3 1/3 DIA x 6 5/8.
- Lastly, insert folded hood assembly in bag (step 4) and close (step 5).

(C) – Bag (step 4) to be constructed of L-P-378 material, as specified in MIL-B-117. The bag (step 4) shall be heat sealed in accordance with the bag or bag material supplier's recommendations for dwell, pressure and temperature requirements. Sufficient air shall be evacuated from the bagged assembly to cause the the bag to be taut and cling tightly to the enclosed item.

(D) – Shelf life markings shall be applied.