

Battery, Primary, Cylindrical -- Lithium Thionyl Chloride  
International Size Reference: C, Standard Termination

Technical Requirements:

1. Nominal Capacity @ 3 mA to 2 V: Minimum of 7 Ah
2. Rated Voltage (nominal): 3.6 V
3. Dimensions:
  - A. Battery Overall Height: 48.5 mm (minimum), 50 (maximum)
  - B. Battery Diameter: 24.9 mm (minimum), 26.2 mm (maximum)
4. Operating Temperature Range: - 40( C to + 65( C
5. Storage Temperature Range: - 50( C to + 70( C
6. Battery Shall Be Recognized By Underwriters Laboratories, Inc. Under UL Standard 1642 As "User-Replaceable."
7. Battery Shall Be Non-Restricted or Shall Meet: (a) the Exemptions of Title 49, Part 173, Section 173.185, Lithium Batteries and Cells and (b) the International Air Transport Association (IATA) Regulations.

SUGGESTED SOURCES OF SUPPLY

CAGE CODE

Part Number

Name And Address

0BYG1

TL-2200

Tadrian Electronic Industries

2 Seaview Blvd. Ste 102

Port Washington, NY 11050-4634

0BYG1

TL-5920

Tadrian Electronic Industries, Inc.

2 Seaview Blvd. Ste 102

Port Washington, NY 11050-4634