

CONTINUATION SHEET	Reference No. of Document Being Continued PIIN/SIIN DAAE20-01-D-0094 MOD/AMD P00002	Page 2 of 4
---------------------------	---	--------------------

Name of Offeror or Contractor: E G PRECISION MFG CO

SECTION A - SUPPLEMENTAL INFORMATION

1. The purpose of this modification is to revise SPI P5-45-4949, Rev A, dated 23 Jan 92 and replace with SPI P5-45-4949, Rev B, undated (Attachment 005).
2. Special Packaging Instructions, Clause DS6411, is changed in Section D of basic contract per Attachment 006.
3. As a result of this modification, there is no change in contract value.
4. All other terms and conditions of the contract remain the same.

*** END OF NARRATIVE A 002 ***

CONTINUATION SHEET	Reference No. of Document Being Continued	Page 3 of 4
	PIIN/SIIN DAAE20-01-D-0094	MOD/AMD P00002

Name of Offeror or Contractor: E G PRECISION MFG CO

SECTION D - PACKAGING AND MARKING

For Local Clauses See: <https://aais.ria.army.mil>

<u>Status</u>	<u>Regulatory Cite</u>	<u>Title</u>	<u>Date</u>
D-1 CHANGED	52.211-4501 TACOM-RI	PACKAGING REQUIREMENTS (SPECIAL PACKAGING INSTRUCTIONS)	FEB/2000
<p>a. Military preservation, packing, and marking shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 Dec 99 and the Special Packaging Instruction contained in the TDP.</p> <p>Preservation: MILITARY Level of Packing: B Quantity Per Unit Package: 001 SPI Number: P5-45-4949, Rev B, not dated</p> <p>b. Unitization Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.</p> <p>c. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and as applicable, unitized loads shall be marked in accordance with MIL-STD-129, Revision N, Date 15 May 97, including bar coding in accordance with ANSI/AIM-BC1, Uniform Symbology Specification Code 39.</p> <p>d. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in paragraph e below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided the contractor notifies the Administrative Contracting Officer.60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to the Contracting Officer and the Administrative Contracting Officer. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.</p> <p>e. SUPPLEMENTAL INSTRUCTIONS: The gross weight and total quantity per pallet shall be placed on a marking board/panel and securely attached on two adjacent sides.</p>			

(End of clause)

(DS6411)

CONTINUATION SHEET**Reference No. of Document Being Continued****Page 4 of 4****PIIN/SIIN** DAAE20-01-D-0094**MOD/AMD** P00002**Name of Offeror or Contractor:** E G PRECISION MFG CO

SECTION J - LIST OF ATTACHMENTS

<u>List of</u> <u>Addenda</u>	<u>Title</u>	<u>Date</u>	<u>Number</u> <u>of Pages</u>	<u>Transmitted By</u>
Attachment 005	SPI P5-45-4949, REV B		2PG	
Attachment 006	REVISED SPECIAL PACKAGING INSTRUCTIONS DS6411		1PG	