





CONTRACT C WORKSHEET

PRON M121A243M1

AMC 1

AMSC G

ATC AWFBD

TDP 12529586

TDPL DATE 07/23/01

NSN 5360121890287

NOMENCLATURE SPRING, HELICAL, COMP

ENGINEERING EXCEPTIONS: The following engineering changes apply to this  
procurement action(s):

No engineering exception.

GFM/GFE: DRAWING NO.

MYLARS REQUIRED (Check one): Y or X N

*Attachment 003*



**Packaging Requirements Sheet**  
**(Special Packaging Instructions) DS6411**

**PRON: M121A235M1**      **DATE: 12 JUN 2001**

**NSN: 5360-01-177-2683**

**MILSTRIP: SUE LERCH/28202**

- A. Military preservation, packing, and marking for the item identified above shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 DEC 99, and the Special Packaging Instruction contained in the TDP.

**PRESERVATION: MILITARY**  
**LEVEL OF PACKING: B**  
**QUANTITY PER UNIT PACKAGE: 001**  
**SPI NUMBER P12304737, DATED 4 OCT 85**

- B. Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.
- C. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129 Revision N, Date 15 May 97, including bar coding iaw ANSI/AIM-BC1, Uniform Symbology Specification Code 39.
- D. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in Paragraph E below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.
- E. SUPPLEMENTAL INSTRUCTIONS: DELETE PPP-T-76 AND REPLACE WITH ASTM D5486. DELETE MIL-P-116 AND REPLACE WITH MIL-STD-2073-1. DELETE MIL-G-10924 AND REPLACE WITH MIL-PRF-10924.

*Attachment 005*

**Packaging Requirements Sheet**  
**(Special Packaging Instructions) DS6411**

**PRON: M121A241M1      DATE: 24 JUL 2001**

**NSN: 1015-12-179-0167**

**MILSTRIP: SUE LERCH/28202**

- A. Military preservation, packing, and marking for the item identified above shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 DEC 99, and the Special Packaging Instruction contained in the TDP.

**PRESERVATION: MILITARY**

**LEVEL OF PACKING: B**

**QUANTITY PER UNIT PACKAGE: 001**

**SPI NUMBER P12529741, REV. D, DATED 11 AUG 97**

- B. Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.
- C. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129 Revision N, Date 15 May 97, including bar coding iaw ANSI/AIM-BC1, Uniform Symbology Specification Code 39.
- D. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in Paragraph E below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.
- E. SUPPLEMENTAL INSTRUCTIONS: DELETE MIL-L-3150 AND REPLACE WITH MIL-PRF-3150. DELETE MIL-P-3420 AND REPLACE WITH MIL-PRF-3420. DELETE MIL-B-117 AND REPLACE WITH MIL-DTL-117.

*Attachment 006*

**Packaging Requirements Sheet**  
**(Special Packaging Instructions) DS6411**

**PRON: M121A243M1      DATE: 1 AUG 2001**

**NSN: 5360-12-189-0287**

**MILSTRIP: SUE LERCH/28202**

- A. Military preservation, packing, and marking for the item identified above shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 DEC 99, and the Special Packaging Instruction contained in the TDP.

**PRESERVATION: MILITARY**

**LEVEL OF PACKING: B**

**QUANTITY PER UNIT PACKAGE: 001**

**SPI NUMBER P12529586, REV. B, DATED 21 APR 89**

- B. Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.
- C. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129 Revision N, Date 15 May 97, including bar coding iaw ANSI/AIM-BC1, Uniform Symbology Specification Code 39.
- D. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in Paragraph E below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.
- E. SUPPLEMENTAL INSTRUCTIONS: DELETE MIL-P-116 AND REPLACE WITH MIL-STD-2073-1. DELETE MIL-L-3150 AND REPLACE WITH MIL-PRF-3150. DELETE MIL-P-3420 AND REPLACE WITH MIL-PRF-3420. DELETE MIL-B-117 AND REPLACE WITH MIL-DTL-117.

*Attachment 007*

**Packaging Requirements Sheet**  
**(Special Packaging Instructions) DS6411**

**PRON: M121A244M1      DATE: 25 JUL 2001**

**NSN: 5360-12-179-2979**

**MILSTRIP: SUE LERCH/28202**

- A. Military preservation, packing, and marking for the item identified above shall be accomplished in accordance with the specific requirements identified below, all the applicable requirements of MIL-STD-2073-1, Revision D, Date 15 DEC 99, and the Special Packaging Instruction contained in the TDP.

**PRESERVATION: MILITARY**  
**LEVEL OF PACKING: B**

**QUANTITY PER UNIT PACKAGE: 001**

**SPI NUMBER P12529677, REV. C, DATED 14 NOV. 90**

- B. Unitization: Shipments of identical items going to the same destination shall be palletized if they have a total cubic displacement of 50 cubic feet or more unless skids or other forklift handling features are included on the containers. Pallet loads must be stable, and to the greatest extent possible, provide a level top for ease of stacking. A palletized load shall not exceed 4,000 pounds and should not exceed 52 inches in length or width, or 54 inches in height. The load shall be contained in a manner that will permit safe handling during shipment and storage.
- C. Marking: In addition to any special markings called out on the SPI, all unit packages, intermediate packs, exterior shipping containers, and, as applicable, unitized loads shall be marked in accordance with MIL-STD-129 Revision N, Date 15 May 97, including bar coding iaw ANSI/AIM-BC1, Uniform Symbology Specification Code 39.
- D. This SPI has been validated and the method of preservation/packing has proven successful in meeting the needs of the military distribution system, including indeterminate storage and shipment throughout the world. Special instructions and/or tailoring of the SPI is detailed in the Supplemental Instructions in Paragraph E below. A prototype package is required to validate the sizes and fit requirements of the SPI. Minor dimensional and size changes are acceptable provided contractor provides the PCO and ACO with notification 60 days prior to delivery. Any design changes or changes in the method of preservation that provide a cost savings without degrading the method of preservation or packing or affecting the serviceability of the item will be considered and responded to within 10 days of submission to PCO and ACO. Government reserves the right to require testing to validate alternate industrial preservation methods, materials, alternate blocking, bracing, cushioning, and packing.
- E. SUPPLEMENTAL INSTRUCTIONS: DELETE MIL-P-116 AND REPLACE WITH MIL-STD-2073-1. DELETE MIL-C-16173 AND REPLACE WITH MIL-PRF-16173. DELETE MIL-B-121 AND REPLACE WITH MIL-PRF-121. DELETE PPP-P-291 AND REPLACE WITH A-A-1051. DELETE MIL-B-117 AND REPLACE WITH MIL-DTL-117.

*Attachment 008*

## DOCUMENT SUMMARY LIST

---

Item: SPRING, HELICAL COMP  
NSN: 5360-01-177-2683  
Control Number/PRON: M121A235

---

Identifies all first tier documents (cited in SOW) (applicable DIDs). Also included are all referenced documents (2nd, (includes DID block 10 references), 3<sup>rd</sup> and lower tier) which have been tailored.

### DOCUMENT CATEGORY:

CATEGORY 0 - Unless otherwise specified in the solicitation, contract, or contract modifications, all documents are for guidance and information only.

CATEGORY 1 - The requirements contained in the directly cited document are contractually applicable to the extent specified. All referenced documents are for guidance and information only.

CATEGORY 2 - The requirements contained in the directly cited document and the reference documents identified in the directly cited document are contractually applicable to the extent specified. All subsequently referenced documents are for guidance and information only.

CATEGORY 3 - Unless otherwise specified in the solicitation, contract or contract modification, all requirements contained in the directly cited document and all reference and subsequently referenced documents are contractually applicable to the extent specified.

Document Number (Contract Reference) Applicable Tailoring	Document Title	Document Date/ Document Category
1a. MIL-STD-2549 Table DIP 4-1	Configuration Management Data Interface	30 Jun 97 Cat 2
1b. DI-CMAN-81554 (seq A001)	Configuration Change Control Data Information Packet	30 Jun 97 Cat 2
2. ANSI/ISO/ASQC Q9003	Quality Systems-Model for Quality Assurance in Final Inspection and Test OR	18 Jul 94
ANSI/ISO/ASQC Q9001-2000	American National Standard Quality management systems- Requirements	13 Dec 00

---

## DOCUMENT SUMMARY LIST

---

Item: SPRING, METAL  
NSN: 1015-12-179-0167  
Control Number/PRON: M121A241

---

Identifies all first tier documents (cited in SOW) (applicable DIDs). Also included are all referenced documents (2nd, (includes DID block 10 references), 3<sup>rd</sup> and lower tier) which have been tailored.

### DOCUMENT CATEGORY:

CATEGORY 0 - Unless otherwise specified in the solicitation, contract, or contract modifications, all documents are for guidance and information only.

CATEGORY 1 - The requirements contained in the directly cited document are contractually applicable to the extent specified. All referenced documents are for guidance and information only.

CATEGORY 2 - The requirements contained in the directly cited document and the reference documents identified in the directly cited document are contractually applicable to the extent specified. All subsequently referenced documents are for guidance and information only.

CATEGORY 3 - Unless otherwise specified in the solicitation, contract or contract modification, all requirements contained in the directly cited document and all reference and subsequently referenced documents are contractually applicable to the extent specified.

Document Number (Contract Reference) Applicable Tailoring	Document Title	Document Date/ Document Category
1a. MIL-STD-2549 Table DIP 4-1	Configuration Management Data Interface	30 Jun 97 Cat 2
1b. DI-CMAN-81554 (seq A001)	Configuration Change Control Data Information Packet	30 Jun 97 Cat 2
2a. MIL-DTL-16232G (TDPL)	Phosphate Coating Heavy Manganese or Zinc Base	07 Jan 00 Cat 2
2b. DI-NDTI-80603 (DD Form 1423)	Test Procedure	01 Jun 88 Cat 1

## DOCUMENT SUMMARY LIST

Item: SPRING, HELICAL, COMP  
 NSN: 5360-12-179-2979  
 Control Number/PRON: M121A244

Identifies all first tier documents (cited in SOW) (applicable DIDs). Also included are all referenced documents (2nd, (includes DID block 10 references), 3<sup>rd</sup> and lower tier) which have been tailored.

### DOCUMENT CATEGORY:

CATEGORY 0 - Unless otherwise specified in the solicitation, contract, or contract modifications, all documents are for guidance and information only.

CATEGORY 1 - The requirements contained in the directly cited document are contractually applicable to the extent specified. All referenced documents are for guidance and information only.

CATEGORY 2 - The requirements contained in the directly cited document and the reference documents identified in the directly cited document are contractually applicable to the extent specified. All subsequently referenced documents are for guidance and information only.

CATEGORY 3 - Unless otherwise specified in the solicitation, contract or contract modification, all requirements contained in the directly cited document and all reference and subsequently referenced documents are contractually applicable to the extent specified.

Document Number (Contract Reference) Applicable Tailoring	Document Title	Document Date/ Document Category
1a. MIL-STD-2549 Table DIP 4-1	Configuration Management Data Interface	30 Jun 97 Cat 2
1b. DI-CMAN-81554 (seq A001)	Configuration Change Control Data Information Packet	30 Jun 97 Cat 2
2. ANSI/ISO/ASQC Q9003	Quality Systems-Model for Quality Assurance in Final Inspection and Test OR	18 Jul 94
ANSI/ISO/ASQC Q9001-2000	American National Standard Quality management systems- Requirements	13 Dec 00
3a. NCSL Z540-1 (ES7010)	General Requirements for Calibration Laboratories and Measuring and Test Equipment OR	30 Aug 94
ISO 10012-1 (ES7010)	Quality Assurance Requirements for Measuring Equipment, Part 1: Metrological Confirmation System	1992
3b. DI-QCIC-81006 (DD Form 1423)	Special Inspection Equipment Descriptive Documentation	11 Sep 89 Cat 1

CONTRACT DATA REQUIREMENTS LIST

DD FORM 1423 (MECHANIZED)

CATEGORY: MISC SYSTEM/ITEM: SPRING, HELICAL COMP  
TO CONTRACT/PR: M121A235

1. SEQUENCE NUMBER		14. DISTRIBUTION	DRFT/REG/REPRO COPIES
2. TITLE OF DATA ITEM			
3. SUBTITLE			
4. DATA ITEM NUMBER			
5. CONTRACT REFERENCE			
6. TECHNICAL OFFICE	7. DD	8. APP	9. DIST STATEMENT
	250	CODE	REQUIRED
10. FREQUENCY	11. AS OF DATE		15. TOTAL:
12. DATE OF 1ST SUBMISSION	13. DATE OF SUBSEQUENT SUBMISSION		
16. REMARKS			

---

1. A001		14. AMSTA-AR-CCL-F (ECALS)	/ / / /
2. CONFIGURATION CHANGE CONTROL*			
3. ENGINEERING ACTIONS			
4. DI-CMAN-81554			
5. SECTION C			
6. AMSTA-AR-ES	7. NO	8. -	9. **
10. ASREQ	11. ---		15. TOTAL 0/ 0/ 0
12. ASREQ	13. ASREQ		

16. REMARKS  
 PREPARE ENGINEERING ACTIONS IAW DI-CMAN-81544 AND SUBMIT ELECTRONICALLY VIA ECALS WORLDWIDE WEB PAGE [HTTP://EDMD4.PICA.ARMY.MIL/](http://EDMD4.PICA.ARMY.MIL/). \*DATA INFORMATION PACKET \*\*DISTRIBUTION STATEMENT WILL BE ASSIGNED AND IMPLEMENTED BY THE DOD CONFIGURATION MANAGER. THE POC FOR ECALS IS LEE SADAUSKAS, AMSTA-AR-QAW, (973) 724-6626 LEES@PICA.ARMY.MIL.

APPROVED BY: STEPHEN J HANSEN, SDMO, AMSTA-AR-QAD

DATE: 06/12/2001

Exhibit A

CONTRACT DATA REQUIREMENTS LIST  
DD FORM 1423 (MECHANIZED)

CATEGORY: MISC SYSTEM/ITEM: SPRING,METAL  
TO CONTRACT/PR: M121A241

1. SEQUENCE NUMBER		14. DISTRIBUTION	DRFT/REG/REPRO COPIES
2. TITLE OF DATA ITEM			
3. SUBTITLE			
4. DATA ITEM NUMBER			
5. CONTRACT REFERENCE			
6. TECHNICAL OFFICE	7. DD 250	8. APP CODE	9. DIST STATEMENT REQUIRED
10. FREQUENCY	11. AS OF DATE		15. TOTAL:
12. DATE OF 1ST SUBMISSION		13. DATE OF SUBSEQUENT SUBMISSION	
16. REMARKS			

---

1. A001		14. AMSTA-AR-CCL-F (ECALS)	/ / / /
2. CONFIGURATION CHANGE CONTROL*			
3. ENGINEERING ACTIONS			
4. DI-CMAN-81554			
5. SECTION C			
6. AMSTA-AR-ES	7. NO	8. -	9. **
10. ASREQ	11. ---		15. TOTAL 0/ 0/ 0
12. ASREQ		13. ASREQ	

16. REMARKS  
PREPARE ENGINEERING ACTIONS IAW DI-CMAN-81544 AND SUBMIT ELECTRONICALLY VIA ECALS WORLDWIDE WEB PAGE [HTTP://EDMD4.PICA.ARMY.MIL/](http://EDMD4.PICA.ARMY.MIL/). \*DATA INFORMATION PACKET \*\*DISTRIBUTION STATEMENT WILL BE ASSIGNED AND IMPLEMENTED BY THE DOD CONFIGURATION MANAGER. THE POC FOR ECALS IS LEE SADAUSKAS, AMSTA-AR-QAW, (973) 724-6626 LEES@PICA.ARMY.MIL.

---

1. A002		14. PROCUREMENT	/ /
2. TEST PROCEDURE/ PHOSPHATE COATING PRE-		CONTRACTING	/ /
3. PRODUCTION PROCEDURE		OFFICER	/ 1/
4. DI-NDTI-80603*			
5. MIL-DTL-16232, PARA 3.1			
6. AMSTA-AR-WEP-RM	7. XX	8. A	9. N/A
10. ONE/R	11. N/A		15. TOTAL 0/ 1/ 0
12. 60 DAC		13. N/A	

16. REMARKS  
BLOCK 8 CONT.-PRIOR TO PRODUCTION, APPROVAL THROUGH THE CONTRACTING OFFICER IS REQUIRED WITHIN 60 DAYS AFTER CONTRACT AWARD. A DD FORM 250 IS NOT REQUIRED FOR PHOSPHATE COATING PROCEDURE APPROVAL. CONTRACTOR FORMAT ACCEPTABLE. SHALL BE SUBMITTED ON AN IBM COMPATIBLE 3-1/2" DISKETTE IN RICH TEXT FORMAT (RTF).

---

APPROVED BY: STEPHEN J HANSEN, SDMO, AMSTA-AR-QAD DATE: 07/25/2001

Exhibit B

CONTRACT DATA REQUIREMENTS LIST

DD FORM 1423 (MECHANIZED)

CATEGORY: MISC SYSTEM/ITEM: SPRING, HELICAL, COMP  
TO CONTRACT/PR: M121A244

1. SEQUENCE NUMBER		14. DISTRIBUTION	DRFT/REG/REPRO COPIES
2. TITLE OF DATA ITEM			
3. SUBTITLE			
4. DATA ITEM NUMBER			
5. CONTRACT REFERENCE			
6. TECHNICAL OFFICE	7. DD	8. APP	9. DIST STATEMENT
	250	CODE	REQUIRED
10. FREQUENCY	11. AS OF DATE		15. TOTAL:
12. DATE OF 1ST SUBMISSION		13. DATE OF SUBSEQUENT SUBMISSION	
16. REMARKS			

---

1. A001		14. AMSTA-AR-CCL-F (ECALS)	/ / / /
2. CONFIGURATION CHANGE CONTROL*			
3. ENGINEERING ACTIONS			
4. DI-CMAN-81554			
5. SECTION C			
6. AMSTA-AR-ES	7. NO	8. -	9. **
10. ASREQ	11. ---		15. TOTAL 0/ 0/ 0
12. ASREQ		13. ASREQ	

16. REMARKS  
PREPARE ENGINEERING ACTIONS IAW DI-CMAN-81544 AND SUBMIT ELECTRONICALLY VIA ECALS WORLDWIDE WEB PAGE [HTTP://EDMD4.PICA.ARMY.MIL/](http://EDMD4.PICA.ARMY.MIL/). \*DATA INFORMATION PACKET \*\*DISTRIBUTION STATEMENT WILL BE ASSIGNED AND IMPLEMENTED BY THE DOD CONFIGURATION MANAGER. THE POC FOR ECALS IS LEE SADAUSKAS, AMSTA-AR-QAW, (973) 724-6626 LEES@PICA.ARMY.MIL.

---

1. A002		14. AMSTA-AR-QAT (D)	(1) / 1/ / /
2. SPECIAL INSPECTION EQUIPMENT DESCRIPTIVE DOC.			
3. AIE DESIGN DOCUMENTATION		QAR	/ /
		CO (LT ONLY)	/ /
4. DI-QCIC-81006*		AMSTA-AR-QAW-C (LT ONLY) (R)	(2) / / / /
5. SECTION E			
6. AMSTA-AR-QA	7. XX	8. A	9. N/A
10. ONE/R	11. N/A		15. TOTAL 0/ 1/ 0
12. **		13. WHEN REV.	

16. REMARKS  
\* BLOCK 4: DO NOT ADDRESS PARAGRAPHS 10.1, 10.2, 10.4.1(f) AND 10.4.2. IGNORE ALL REFERENCE TO THE WORD "SPECIAL" IN DID. SUBMIT FOR ALL CRITICAL, SPECIAL AND MAJOR CHARACTERISTICS IN SPECIFICATION OR QAP. \*\* BLOCK 12: SUBMIT 30 DAYS PRIOR TO FA, OR PRODUCTION, IF FA IS WAIVED. THE GOVERNMENT WILL RESPOND WITHIN 30 DAYS OF RECEIPT OF ORIGINALS AND REVISIONS. REVISIONS ARE TO BE SUBMITTED WITHIN 10 DAYS OF RECEIPT OF GOVERNMENT RESPONSE. IF DOCUMENTATION WAS APPROVED ON PRIOR CONTRACT AND NO CHANGES WERE MADE, SUBMIT

ONLY EVIDENCE OF PRIOR APPROVALS.

email: (1)aie-qat@pica.army.mil (2)amsta-ar-qa-cdrl@ria-emh2.army.mil

Text:Microsoft Office 97

Drawings:AutoCAD-Release 14 (Expressed mailed hard copies will be accepted)

Files may be compressed using ZIP program.

WARNING: Large packages may cause delays in delivery using mail internet.

Email subject line must contain end item nomenclature.

---

APPROVED BY: STEPHEN J HANSEN, SDMO, AMSTA-AR-QAD

DATE: 07/25/2001