


NOT APPLICABLE FOR INTERPLANT SHIPMENT (A)				NATIONAL STOCK NUMBER 4240-01-399-3349			
SPECIAL PACKAGING INSTRUCTION (AMCCOM Suppl 1 to AR 700-15)				NOMENCLATURE Carrier Assembly			
UT EA (B)		CLEANING/DRYING C1/ANY		SPI NUMBER (PN) P5-1-2775			
LEVEL A UNIT PACK REQUIREMENTS (MIL-P-116 METHOD III*)	STEPS	DRAWING OR SPECIFICATION	STYLE	TYPE	GRADE	CLASS	SIZE AND REMARKS (INCHES)
* PREPARE CARRIER PER NOTE C BELOW							
LEVEL B (METHOD) <input checked="" type="checkbox"/> NOT APPLICABLE <input type="checkbox"/> SEE NOTE <input type="checkbox"/> IAW MIL-STD-2073-1 LEVEL C (METHOD) <input checked="" type="checkbox"/> NOT APPLICABLE <input type="checkbox"/> SEE NOTE <input type="checkbox"/> IAW MIL-STD-2073-1 COMMERCIAL PACKAGING <input checked="" type="checkbox"/> NOT APPLICABLE <input type="checkbox"/> SEE NOTE <input type="checkbox"/> IAW ASTM D3981							
UNIT PACK LOGISTICS DATA (Weights and Sizes Approximate)							
LEVEL	UNIT PACK QUANTITY	UNIT PACK WEIGHT	UNIT PACK CUBE	UNIT PACK SIZE (EXTERIOR) FEET			
A	1	.88 lbs.	.188 cu. ft.	1.13 x 1.04 x .16			
Intermediate packaging and packing will be in accordance with specification MIL-STD-2073-1 or as otherwise specified hereon.							
Marking will be in accordance with MIL-STD-129 (D)							
Specifications, standards, and drawings listed hereon of the issue in effect on date of invitation for bid form a part of this data sheet. The applicable general and referenced requirements of specification MIL-STD-2073-1 form part of this data sheet. Unless otherwise specified, materials will be minimum size IAW MIL-STD-2073-1.							
Tolerances shall be in accordance with material specifications. Quality performance and testing requirements shall be in conformance with MIL-STD-2073-1 or as specified hereon. (E)							
REMARKS/ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.							
<p>(A) - Interplant shipment. Packaging and marking for interplant shipment is for supplies and materials that do not directly enter the military supply system. Typical interplant shipments are shipments from a vendor to a subcontractor or a prime contractor, or between contractors and subcontractors, or from a vendor or contractor to a military arsenal, plant, or other activity for evaluation, immediate use, or further processing as specified in the applicable contract.</p> <p>(B) - Each unpackaged carrier shall be considered a unit pack.</p> <p>(C) - Prior to packaging, store straps and close openings in carrier with hook and pile fasteners provided, as shown in sketch on page 2.</p>							
Prepared by: <i>jerry d. stallings / mar 95</i>				Revised by:			
ITEM DATA (APPROX) ITEM CODE - Z55	CBDCOM 81361						
ITEM SIZE - 13 1/2 x 12 1/2 x 1 7/8 inches	SCBRD-ENE-S						
ITEM WEIGHT - .88 lbs.	PAGE NUMBER	NUMBER OF PAGES	APPROVAL	REVISION	DATE		
	1	2	<i>JA</i>	S5H1506 -0033	Y73-028	30 Mar 95	

AMCCOM FORM 357-R, 1 AUG 84 DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

NOM
C
AMC



SPECIAL PACKAGING INSTRUCTION(Continued)


NATIONAL STOCK NUMBER
4240-01-399-3349

SPI NUMBER (PIN)
P5-1-2775

- (D) - Mark unit assembly using paper or cloth shipping tag in accordance with applicable requirement in MIL-STD-129. Utilize twine to fasten tag to carrier. Securely fasten tag to O-RING "A" as shown in sketch below.
- (E) - The preproduction (first article) and quality conformance inspection and testing requirements for intermediate packaging shall be in accordance with EA-C-1880; packing inspection shall be in accordance with MIL-STD-2073-1.

UNIT PACK ASSEMBLY

(SEE CORRESPONDING UNIT PACKAGE REQUIREMENTS HEREIN)



NOTES:

1. FOLD AND STORE STRAPS "A" AND "B" INTO OPENING OF CARRIER.
2. FASTEN HOOK SNAP OF STRAP "C" TO O-RING B.
3. WHILE CLOSING CARRIER FLAP, TUCK STRAP "D" UNDER FLAP AND CLOSE CARRIER OPENING WITH HOOK AND PILE FASTENER PROVIDED.
4. DRAWING NOT TO SCALE; FOR REFERENCE ONLY.

NOMENCLATURE
Carrier Assembly

PAGE NUMBER
2

NUMBER OF PAGES
2